



**USED FOR HOME AND INDUSTRIAL FENCING,
AIRPORTS, HIGHWAYS, MILITARY COMPOUNDS,
SPORTS COMPLEXES, ELECTRICTY TRANSFORMERS ETC.**



1148

**Quality & Durability
Trusted Since 1965**

CHAIN LINK

STANDARD SPECIFICATIONS

(ZINC COATED AND PLASTIC COATED STEEL CHAIN LINK FENCING - SLS 1148)

PVC WIRE SPECIFICATION

Gauge	Core Wire	Mesh Wire (PVC Coated)	Tolerance - Overall Thickness	Mass of Zinc Coating	Plastics
12	1.9mm	2.65mm	+/- 0.15	CLASS D * Also available in Class A	GRADE A
10	2.24mm	3.15mm	+/- 0.15		
8	3.0mm	4.0mm	+/- 0.20		
6	3.55mm	4.75mm	+/- 0.20		

STANDARD MESH SIZE (OPENING)

mm	Tolerance	Nominal Wire Diameter	Tolerance in Height - mm
40	+/- 4.0mm	1.9/2.65, 2.24/3.15	+/- 30
50	+/- 4.5mm	1.9/2.65, 2.24/3.15, 3/4, 3.55/4.75	+/- 40
60	+/- 5.0mm	1.9/2.65, 2.24/3.15, 3/4, 3.55/4.75	+/- 50

Also available in 38mm, 57mm, 63mm openings

STANDARD SIZES OF PVC COATED AND GALVANIZED CHAINLINK FENCING

Standard Height		Open area 2" x 2"			
Metres	Nearest Feet	Gauge of Wire			
		6	8	10	12
1.00	3'.3"	✓	✓	✓	✓
1.20	3'.11"	✓	✓	✓	✓
1.50	4'.11"	✓	✓	✓	✓
1.80	5'.11"	✓	✓	✓	✓
2.00	6'.7"	✓	✓	✓	✓
2.10	6'.11"	✓	✓	✓	✓
2.40	7'.10"	✓	✓	✓	✓
3.00	9'.10"	✓	✓	✓	x
3.60	11'.9"	✓	✓	✓	x
4.00	13'.2"	✓	✓	✓	x

- The wire used in all Macson products are hot dipped galvanized.
- Special orders could also be manufactured to customer specifications.



SINCE 1965

Macson Mesh Industries (Pvt) Ltd

304 Deans Road, Colombo 10, Sri Lanka Tel: +94 11 7437140, +94 11 2684848

Fax: +94 11 7437180 Email: info@macsonmesh.com Web: www.macsonmesh.com